

Data Sheet

Remote Control IKORE Transmitter

The IKORE remote control is highly customizable with many features and accessories. These remote controls also support the operator with an ergonomic design that allows for safe and efficient operation.

Features

- High sensitivity two-step push button
- External removable EEPROM SIM
 module
- Frequency management against interferences
- Hoist selection push button

2.4 GHz

• Radio communication at 2.4 GHz

Benefits

- Easy and fast maintenance
- High resistance to impacts
- Improved ergonomics

Applications

- Used in lifting applications
- Used in crane applications

Comprehensive technical literature is online at *www.danfoss.com*









Technical data

| Description | Value |
|----------------------------------|--|
| Stop function | Cat. 3-Ple EN12849-1 and SIL 3 IEC 61508 / IEC 62061 |
| Ingress Protection rating | IP65/NEMA4 |
| Anti-condensation system | N/A |
| Frequency band | 2.4 GHz |
| Main mechanisms (maximum number) | Push button (7) |
| Removable EEPROM | External |
| Battery model | 4 AAA |
| Battery life | >80hr (100% duty cycle) |
| Operating temperature range | -20 °C to 70 °C (-4 °F to 158 °F) |
| Weight (with battery) | 315 grams |
| Harness | Hand strap/shoulder strap |
| Display | N/A |
| Cable connector | N/A |
| Range limiter | N/A |
| Associated receivers | R11 |

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.